

3750 West Indian School Road Phoenix, Arizona 85019-3518 (602) 636-6720 (800) 644-9131 (602) 636-6724 Fax www.xcelsurfaces.com

TECHNICAL DATA SHEET- TRAVERTINE & PAVER GROUT

DESCRIPTION AND USE

Xcel Surfaces TRAVERTINE & PAVER GROUT

(TPG) is a special blend of cements, sands, polymer and additives specifically formulated for use in locking travertine or concrete pavers in place. When cured, TPG forms a solid grout that will prevent grass and weed growth, insect mining and erosion between pavers. TPG exhibits superior strength, aiding in the prevention of pavers movement. TPG can also be used for vertical applications.

SURFACE PREPARATION

Surface area is clean, dry and joints are free of excess debris. (Caution: Do not apply when pavers or stones are damp as grout will not bond to the surface.)

APPLICATION

Use TPG for typical joint width of $1/8" - \frac{3}{4}"$. Pour the TPG evenly over the area to be grouted; sweep over the joints repeatedly until they are completely filled with sand. Compact TPG into paver joints. Remove all excess TPG from paver surface prior to wetting. Dampen paver joints with a fine mist. Avoid flooding or pooling water on joints. Repeat 3-4 misting applications in 10-15 minute intervals after initial saturation.

PACKAGING

45 lb Bag

COVERAGE

325-350 square feet when using on a typical 6" x12" paver surface with an average width of approximately 1/8" wide.

HANDLING & STORAGE

Mix well before use. Read M.S.D.S. before application. Dispose of unused material in accordance with Federal, State and Local regulations. Storage temperature: (45°-85° F). DO NOT LET PRODUCT FREEZE.

Xcel surfaces products are intended for professional use only. Keep away from children. Xcel Surface warrants its products to be free of manufacturing defects and comply with current published physical properties when applied in accordance with Xcel Surfaces directions and tested in accordance with ASTM and Xcel Surfaces standards. There are no other warranties by Xcel Surfaces of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product. Xcel Surfaces shall not be liable for damages of any sort, including remote or consequential damages resulting from any claimed breach of any warranty, whether expressed or implied, including any warranty of merchantability or fitness for a particular purpose or from any cause whatsoever. Xcel Surfaces shall also not be responsible for use of this product in a manner to infringe on any patent held by others.

> © XCEL SURFACES 2008 All rights reserved. Made in the USA